


# AdBlue Titanium 5l ,10 l, 20 l

AdBlue is a registered trademark for a diesel exhaust fluid (DEF), which is used in diesel engines equipped with selective catalytic reduction (SCR) technology to reduce harmful emissions of nitrogen oxides (NOx). AdBlue is primarily composed of urea (32.5%) and deionized water (67.5%).



AdBlue has become an essential component in modern diesel vehicles, ensuring they comply with environmental regulations while maintaining performance and efficiency.

Capacities	Number of units per carton	Number of units per pallet	Art. no.	Barcode	Kod QR
5 Liter	1	120	221819	5905033221819	

## AQUEOUS UREA SOLUTION AUS 32

Product specification	Monomai k standard
1. Mass fraction of urea, %	31.8 — 33.2
2. Density at 20 °C, kg m	1087.0 — 1093.0
3. Refractive index at 20 °C	1.3814 — 1.3843
4. Alkalinity as mass fraction of NH <sub>3</sub> , %, max	0.2
5. Mass fraction of biuret, %, max	0.3
6. Mass concentration of aldehydes, mg/kg, max	5
7. Infusible particles, mg/kg, max	20
8. Mass concentration of phosphates, ing/kg, max	0.5
9. Mass concentration of aluminium, mg/kg, max	0.5
10. Mass concentration of calcium, mg kg, max	0.5
11. Mass concentration of iron, mg/kg, max	0.5
12. Mass concentration of copper, mg. kg, max	0.2
13. Mass concentration of zinc, mg/kg, max	0.2
14. Mass concentration of chromium, mg/kg, max	0.2
15. Mass concentration of nickel, mg/kg, max	0.2
16. Mass concentration of magnesium, mg/kg, max	0.5
17. Mass concentration of sodium, ing/kg, max	0.5
18. Mass concentration of potassium, mg kg, max	0.5
19. Identity, YES NO	YES
Pastaba. Aqueous urea solution meets ISO 22241-1 requireinents.	

**Mail:** [biuro@hipernet.com.pl](mailto:biuro@hipernet.com.pl)

**Tel.:** 22 679 01 45



Hipernet Sp. z o.o. Sp. Kom.  
Promienna 4/403-672 Warsaw